WRANGLER TJ/ WRANGLER UNLIMITED

ARB DELUXE BULL BARS & WINCH BARS						
YEAR	MODEL	FEATURES	WINCHES	PART NO.		
1997-06	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, TOW POINTS, BLACK	9.5TI/SI, HS9500I, XD9000, XD9000I, M8000, XP9500	3450070		

IPF LIGHTING & ACCESSORIES				
YEAR	RECOMMENDED LIGHTING			
1997-06	800XSD, 900XS, 900HID, 868CS, 968CSG			
1997-06	920HJKTJ - H4 HEADLIGHT CONVERSION KIT WITHOUT BULBS ¹			

¹ IPF M002 HEADLIGHT UPGRADE HARNESS RECOMMENDED WHEN INSTALLING HIGH PERFORMANCE H4 BULBS

ARB ROCK SLIDERS/SIDE RAILS/STEPS				
YEAR	DESCRIPTION	PART NO.		
1997-06	ROCK SLIDERS FOR SWB TJ, BLACK ¹	4450010		

¹ FITS SHORT WHEEL BASE MODEL ONLY

ARB REAR PROTECTION BUMPER				
YEAR	DESCRIPTION	PART NO.		
1997-06	DELUXE REAR BAR ASSEMBLY, BLACK	5650010 ^{1,2}		
	SWINGAWAY WHEEL CARRIER, BLACK	5750012 ^{1,2}		
	OPTIONAL IPF REVERSE LIGHT	8161		
	OPTIONAL HI-LIFT JACK BRACKET, BLACK	5750030		
	OPTIONAL WHEEL LOCK NUT SET	5750040		

^{***} CONTACT ARB WITH ANY QUESTIONS BEFORE ORDERING

REAR BAR HAS BUILT IN TOW HITCH, BUT DOES NOT COME WITH BALL MOUNT FOR TOWING. USE STANDARD 2" RECEIVER AND BALL AVAILABLE AT MOST AUTO PARTS STORES

SAFARI SNORKEL					
YEAR	RECOMMENDED SNORKEL	PART NO.			
09/99-06	4.0L, PETROL, RIGHT SIDE MOUNT1	SS1055HF ^{1,2}			
TO 8/99	4.0L, PETROL, RIGHT SIDE MOUNT1	SS1050HF ^{1,2}			

SNORKEL WILL INTERFERE WITH REMOVAL OF DOORS.

² 4CYL MODELS MAY NEED MODIFICATION

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1997-06	FRONT	DANA 30	29.5 (1.16")	27	3.73 & UP	RD100
				27	3.54 & DN	RD101
			33.3 (1.31")	30	3.73 & UP	RD104
		DANA 44, TJ RUBICON MODEL ONLY			SEE BELOW ³	
1997-06 REAR		DANA 35, C-CLIP, XJ, YJ, ZJ, TJ, WJ	29.5 (1.16")	27	2.73-3.31	RD103
					3.54 & UP	RD1024
				30	3.54 & UP	RD105
		DANA 44 ³	33.3 (1.31")	30	3.92 & UP1	RD116
				30	3.73 & DN	RD117 ²
			_	33	3.92 & UP	RD113
			-	35	3.92 & UP	RD109
		DANA 44, TJ RUBICON MODEL ONLY			SEE BELOW ³	

 $^{^{\}rm 1}$ $\,$ Some Dana 44 with 4.10 ratio use thick ring gear and must use RD117.



REAR BAR AND WHEEL CARRIER MUST BE PURCHASED TOGETHER FOR PROPER INSTALLATION

² Newer OME Dana 35 & Dana 44 ring gears have 7/16" bolts. Flange holes of the Air Locker must be reamed larger to suit.

Most Dana 44 Rubicon's use RD117 with original gears. When using aftermarket or non-stock gears, contact ARB for which locker to use

⁴ Some Dana 35's 4.10 gear sets, may require a high speed carrier air locker. (RD103)

WRANGLER TJ/WRANGLER TJ UNLIMITED

OLD MAN EMU SUSPENSION SYSTEMS						
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.
97-06 SWB	COMPLETE	STOCK/LIGHT LOAD (0-90LBS)	KIT	2"	1	OMETJLKS ^{8,10}
	KITS	HEAVY LOAD (90-180LBS)	KIT	2"	1	OMETJHKS ^{8,10}
		STOCK/LIGHT LOAD (0-90LBS)	KIT	2"	1	OMETJLK ^{9,10}
		HEAVY LOAD (90-180LBS)	KIT	2"	1	OMETJHK ^{9,10}
1997-06	FRONT (6 CYL.)	STOCK/LIGHT LOAD (0-90LBS)	SPRING	2.0"	1	293210
		NITROCHARGER SPORT	SHOCK		2	60046
		NITROCHARGER	SHOCK		2	*N66/N66C
1997-06	FRONT (6 CYL.)	HEAVY LOAD (90-180LBS)	SPRING	2.0"	1	293310
		NITROCHARGER SPORT	SHOCK		2	60047
		NITROCHARGER	SHOCK		2	N66
1997-06	REAR	LIGHT LOAD/SOFT TOP	SPRING	2.5"	1	29413,10
		NITROCHARGER SPORT	SHOCK		2	60048
		NITROCHARGER	SHOCK		2	N67
1997-06	REAR	MEDIUM LOAD/HARD TOP	SPRING	2.0"	1	29413,10
		NITROCHARGER SPORT	SHOCK		2	60048
		NITROCHARGER	SHOCK		2	N67
1997-06	REAR	HEAVY CONSTANT LOAD (220 TO GVW)	SPRING	2.0"	1	29423,10
		NITROCHARGER SPORT	SHOCK		2	60048
		NITROCHARGER	SHOCK		2	N67
1997-06	REAR	HEAVY CONSTANT LOAD (220 TO GVW)	SPRING	2.0"	1	29493,10
UNLIMITED		NITROCHARGER SPORT	SHOCK		2	60049
MODELS		NITROCHARGER	SHOCK		2	N67
1997-06	REQUIRED FOR	T-CASE SPACER KIT (1997-02)			1	JWGK01 ^{1, 6}
		T-CASE SPACER KIT (2003 ON W/ MANUAL	TRANSMISSION)		1	JWGK02 ^{1, 6}
	INSTALLATION	T-CASE SPACER KIT (2003 ON W/ AUTOMAT	IC TRANSMISSIC	N)	1	JWGK03 ^{1, 6}
		PANHARD ROD BRACKET			1	FKWTJ02 ^{2,6}
		BUMP STOP SPACER KIT			1	FK16 ^{3,6}
		STEERING DAMPER			1	OMESD40
	OPTIONAL	FRONT 10MM TRIM SPACER				OMEJGF10
		REAR 10MM TRIM SPACER				OMEWTJPR10
	ALSO	FRONT EXTENDED LENGTH NITROCHARGE	ER SPORT SHOC	KS	2	60047L⁵
	AVAILABLE	REAR EXTENDED LENGTH NITROCHARGE	R SPORT SHOCK	S	2	60049L⁵
		4" FRONT COIL SPRING			1	29397,10
		4" REAR COIL SPRING			1	29467,10
		JEEP UNLIMITED REAR COIL SPRING (CON	STANT 400LBS)		1	299610
		Appropriate T Core optobe MIT to MAND ITODY TO DESCRIP				

- APPROPRIATE T-CASE SPACER KIT IS MANDATORY TO PREVENT DRIVELINE VIBRATION.
- 2 $\,$ FKWTJ02 Panhard Rod Bracket is mandatory to ensure correct rear axle tracking.
- ³ FK16 SPACER KIT IS MANDATORY TO PREVENT COIL SPRINGS FROM BECOMING SOLID ON FULL COMPRESSION.
- 4 $\;$ Due to a variance in curb weight, 4 cylinder models may net slightly more lift than 6 cylinder models.
- 5 60047L/60049L EXTENDED LENGTH SHOCKS ARE FOR 3.5-5" SUSPENSION LIFTS ONLY AND ARE NOT INTENDED FOR USE WITH ANY OLD MAN EMU SYSTEMS. MODIFIED BUMP STOPS ARE REQUIRED.
- 6 IMPORTANT: FK16, FKWTJ02 & JWGK01 ARE ALL MANDATORY FOR PROPER INSTALLATION. FAILURE TO INSTALL ANY OF THESE KITS WILL VOID OME WARRANTY.
- $^{7}\quad$ 4" Coils match L Series shocks, but do not constitute a complete system
- ⁸ KIT CONTAINS OLD MAN EMU NITROCHARGER SPORT SHOCKS
- 9 Kit contains standard Old Man Emu Shocks
- Due to a variance in curb weight, Rubicon models may not gain the full advertised lift height



WRANGLER TJ/WRANGLER TJ UNLIMITED

ARB AIR LOCKER DIFFERENTIAL COVERS				
YEAR	DESCRIPTION	PART NO.		
DANA 44	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750003 ^{2*}		
DANA 30	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750002 ^{1*}		
DANA 35	HTTP://ARBUSA.COM/NEW_PRODUCTS/DIFFERENTIAL_COVER.PDF	0750004*		

- WILL NOT WORK WITH STOCK HEIGHT VEHICLES
- ² WILL NOT WORK WITH RUBICON MODELS
- INTERNAL DIFF COVER MODIFICATIONS MAY BE NECESSARY WITH SOME R&P RATIOS IF CONTACT WITH COVER OCCURS

THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT					
YEAR	DESCRIPTION	PART NO.			
1997-06	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT (UNLIMITED MODELS ONLY)	TA50060 ^{1,2}			

- 1 Requires drilling the into the hardtop. Professional installation recommended
- $^2\,$ $\,$ Tracks will need to be cut to 54" length

