TACOMA

YEAR	MODEL	FEATURES	WINCHES	PART NO.
1995-04	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, URETHANE BUFFERS, TOW POINTS, BLACK	9.5XP, HS9500, XD9000, M8000	3423020
2005-11	WINCH BAR	AIRBAG APPROVED, RECESSED INDICATORS, URETHANE BUFFERS, BLACK	9.5XP, HS9500, XD9000, M8000	3423030
2005-11	WINCH BAR	AIRBAG APPROVED, OPTIONAL ARB FOG LIGHTS ¹ , RECESSED INDICATORS, URETHANE BUFFERS, BLACK	9.5XP, HS9500, XD9000, M8000	3423130

ARB Fog Lamp kit part no. 6821201. (MD02) Loom (180209) Switch & (180215) Cap required when fitting 6821201 to models without OE Fog Lamps

IPF LIGHTING & ACCESSORIES				
YEAR	MODEL	RECOMMENDED LIGHTING		
1995-04	3423020	800XSD, 900XS, 900HID, 868CS, 968CSG		
2005-11	3423030	800XSD, 900XS, 900HID, 868CS, 968CSG		
2005-11	3423130	800XSD, 900XS, 900HID, 868CS, 968CSG		

SAFARI SNORKEL					
YEAR	RECOMMENDED SNORKEL	PART NO.			
1995-04	TOYOTA TACOMA V6 SNORKEL	SS170HF			
2005-11	NOT AVAILABLE	N/A			

REFER TO WWW.SAFARI4x4.COM.AU FOR DETAILS.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES						
YEAR	AXLE	DESCRIPTION	SHAFT	SPLINE	RATIO	PART NO.
1996-04	FRONT	7.5" DIA. RG, 10 BOLT, IFS	28 (1.1")	27	ALL	RD90
2005-11	FRONT	8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.91 & UP	RD111
		8" DIA. RG, IFS, 53MM BEARING ID	33 (1.31")	30	3.73 & DN	RD121
1996-11	REAR	8.4" DIA. RG, 12 BOLT	33 (1.31")	30	ALL	RD129

^{**}THESE LOCKERS SUIT OPEN DIFFERENTIALS ONLY, AND WILL NOT REPLACE THE FACTORY E-LOCKER UNLESS THE HOUSING AND 3RD MEMBER ARE REPLACED WITH OPEN END DIFFS.

ARB ROOF RACKS						
YEAR	MODEL	DESCRIPTION	PART NO.			
2005-09	TACOMA	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT	TA23010			
1995-04	TACOMA	THULE ROOF RACK SYSTEM TO SUIT ARB ROOFTOP TENT	T422XT			



TOYOTA

TACOMA

OLD MAN EMU SUSPENSION SYSTEMS							
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
1998-04	COMPLETE	STOCK/LIGHT LOAD (0-110LBS)	KIT	2"	1	OMETAC04LK⁵	
	KITS	HEAVY LOAD (110-220LBS)	KIT	2"	1	OMETAC04HK⁵	
		STOCK/LIGHT LOAD (0-110LBS)	KIT	2"	1	OMETAC04LKS ⁶	
		HEAVY LOAD (110-220LBS)	KIT	2"	1	OMETAC04HKS ⁶	
	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	1.75"	1	2880¹	
		NITROCHARGER SPORT	STRUT		2	90004	
		HEAVY LOAD (110-220LBS)	SPRING	1.75"	1	2881¹	
		NITROCHARGER SPORT	STRUT		2	90004	
	REAR	MEDIUM LOAD	SPRING	2.25"	2	CS046RA/B ²	
		NITROCHARGER SPORT	SHOCK			60062	
		NITROCHARGER	SHOCK		2	*N85/N94	
	REQ'D FOR INSTALLATION	REAR LEAF SPRING BUSHING KIT			2	OMESB89 ³	
		EXHAUST BRACKET			1	FK21 ⁴	
	OPTIONAL	FRONT TRIM SPACER 5MM			1	OME95PF5	
		REAR GREASABLE SHACKLE KIT			1	OMEGS12 ³	
		REAR GREASABLE BUSHING KIT			2	OMESB88 ³	
		EXTRA LEAF			1	D6XL ⁷	

OME FRONT COILS CAN ONLY BE INSTALLED WITH OME NITROCHARGER STRUTS AND COIL SEATS.

FIRMER SHOCK

OLD MAN EMU SUSPENSION SYSTEMS							
MODEL	LOCATION	DESCRIPTION	TYPE	LIFT	QUANTITY	PART NO.	
2005-11	COMPLETE KITS	STOCK/LIGHT LOAD (0-110LBS)	KIT	2"	1	OMETAC05LK⁵	
		HEAVY LOAD (110-220LBS)	KIT	2"	1	OMETAC05HK⁵	
	FRONT	STOCK/LIGHT LOAD (0-110LBS)	SPRING	1.75"	1	28854	
		NITROCHARGER SPORT	SHOCK		2	90000	
		HEAVY LOAD (110-220LBS)	SPRING	1.75"	1	28864	
		NITROCHARGER SPORT	SHOCK		2	90000	
	REAR	MEDIUM LOAD (0LBS TO GVW)	SPRING	2.75"	2	CS047R1	
			SHOCK		2	N182	
	REQ'D FOR INSTALLATION	FITTING KIT			1	FK29 ³	
		U BOLTS			4	OMEU53A	
	OPTIONAL	EXTRA LEAF			1	D29XL ²	
		REAR SPRING BUSHING KIT				OE ²	

¹ NOTE: OE LEAF SPRING BUSHES REQUIRED. USE TOYOTA PART NUMBER 90389-A0003 (QUANTITY OF 8 TOTAL)



FOR LIGHT LOAD APPLICATIONS, THE 2ND LEAF FROM THE BOTTOM OF THE SPRING PACK CAN BE REMOVED FOR IMPROVED RIDE COMFORT. CS046RA/B REAR LEAF SPRINGS ONLY FIT POST 1998 XTRA CAB AND DOUBLE CAB MODELS.

³ OMESB89 must be used with original shackles. OMESB88 must be used with OMEGS12 greasable shackles. OE rubber bushings are used at fixed end of spring. Install original OE bushings from OE springs if they are in good condition, or source new OE bushings from dealership.

⁴ FK21 Exhaust Bracket is a mandatory fitment to ensure exhaust system clears springs.

⁵ Kit contains standard Old Man Emu Nitrocharger Shocks

 $^{^{\}rm 6}$ Kit contains Old Man Emu Nitrocharger Sport Shocks

ADD EXTRA LEAF TO REAR SPRING PACK WHEN CARRYING 220LBS AS A HEAVY CONSTANT LOAD.

 $^{^{2}}$ Add XL to raise spring 15mm and increase rate. Removed leaf 3 to lower spring 15mm and reduce rate

DRIVESHAFT PACKER KIT IS DESIGNED TO SPACE DOWN CARRIER BEARING TO REDUCE TAIL SHAFT FLANGE ANGLE, THEREBY REDUCING DRIVELINE VIBRATION.

⁴ OME FRONT COILS CAN ONLY BE INSTALLED WITH OME NITROCHARGER STRUTS AND COIL SEATS.

 $^{^{\}rm 5}$ $\,$ Kit contains standard Old Man Emu Nitrocharger Shocks